

# CONCEPT 201 Compact HTD

200



► concept 201 C htd

## SPECIFICATIONS

### ○ TECHNICAL DATA :

Dimensions (WxLxH) :	155 x 211 x 126 cm ( 61 x 83 x 49 in )
Weight :	880 kg
Power supply :	400 V 3Ph/N/Pe 50/60 Hz 8,2 kW 12 A 230 V 3Ph/Pe 50/60 Hz 8,2 kW 20 A
Maximum plate size :	26 x 32 inches / 660 x 810 mm
Plate thickness :	Up to 0.276 inches / 7 mm
Compressed air supply :	6 bar minimum

### ○ COMPACT « ALL IN ONE » :

- . All sections are PLC controlled.
- . User friendly touchscreen display for easy operation.
- . Visual representation of machine on screen.

### ○ PROCESSOR :

- . Automatic plate washout and cleaning.
- . Rotary brushes, with combined rotating and oscillating movements.
- . Permanent self-adhesive plate fixing, no punching.
- . Integrated heater- chiller for solvent temperature regulation
- . Automatic solvent replenishment.
- . Solvent fume exhaust system.

### ○ EXPOSURE :

- . 18 UVA lamps 60W 10/R in drawer type exposure.
- . Electronic ballasts
- . High and uniform UV output.
- . Cooling fan, automatic lamp temperature regulation.
- . 20 memory channels, working hours counter.
- . Easy replacement of lamps on pull-out drawer.
- . Heat exhaust system

### ○ LIGHT FINISHER / POST EXPOSURE :

- . 11 UVC lamps 75W.
- . 12 UVA lamps 60W.
- . Electronic ballasts
- . 20 memory channels.
- . Exhaust system.

### ○ DRYER HTD technology

- . 2 drawers with HTD lamps
- . Fume exhaust system.
- . Timer for each drawer.